

Pro-Span[®]

Expansion Repair Coupling







Featuring patented
Grip-Lock[™] that
locks spigot to body
for effective gluing

Redundant internal
dual-seal for safety

Easy-Grip bars for
improved handling
with wet hands

True-Cut feature
ensures perfect cut
to size every time

Pro-Span® Expansion Repair Coupling

FEATURES	BENEFITS
Grip-Lock (Patented) Patented internal rotational lock of spigot to body	Flo Control's patented "locking" feature allows the use of the body as a handle to glue both ends of the repair coupling onto the broken pipe. No other repair coupling allows the use of the body to glue both joints.
Dual-Seal A redundant seal design for safety! 	Stop the leak before it starts! Not all Repair Couplings include two seals!
Glue-Well Internal "trap" for excess glue on the socket end. 	Ensures glue stays where it should, so you don't get "stuck" with a glued-together repair coupling.
Easy-Grip Eight "bars" with "easy to grip" edges and increased holding area 	Positive grip for wet and muddy hands. Easier to twist while pushing or pulling when gluing. This is now the best grip of any repair coupling available.
True-Cut Cutting the damaged pipe section to the length of the compressed coupling positions the piston 	"True-Cut" automatically positions the piston seals in the body correctly. The correct position eliminates potential joint-separation stress caused by temperature swings, ground movement, or changes in line pressure. With True-Cut you get a perfect installation every time.

6.2010

