



# Product Catalog



## ONSITE WASTEWATER TREATMENT SYSTEMS

Infiltrator offers a broad range of products that provide solutions for almost any onsite wastewater system, including:

Drainfields  
Septic Tanks  
Pump Tanks

Holding Tanks  
Site Drainage  
Advanced Treatment

Pump Control Panels  
Treatment Plants


### About Infiltrator Water Technologies

A proven leader with over 38 years of experience in the wastewater industry and an array of onsite water management products that allow for faster and more reliable installations.

**Quality, reliability and innovation are the cornerstones of our success.** Infiltrator chamber systems, tanks, risers, advanced wastewater treatment systems, Aquaworx products, and EZflow septic and drainage systems allow the Infiltrator customer one proven, reliable source for nearly all of their onsite wastewater needs.

**Wastewater can be treated by a centralized wastewater treatment plant or by an onsite septic system.** About 25% of homes in the United States and Canada rely on an onsite septic system for wastewater treatment.

**A septic system has two components:** a septic tank and a leachfield or drainfield (soil absorption field). Primary treatment occurs in the septic tank, where bacteria digest organic materials in the wastewater. The effluent then flows into the leachfield for secondary treatment. Here, bacteria complete the digestion and purification process as the wastewater slowly leaches or infiltrates into the soil. Onsite systems for recycling wastewater have become a sustainable long-term solution in places where community public sewer systems are not physically or financially viable. Onsite systems make efficient use of space as land development puts new pressures on natural resources.





# Reimagining Onsite Water Management



Innovation Since 1987



Drainfield and Tank Products are Manufactured with Recycled Material



ISO 9001 Accredited Manufacturing Facilities



Product Approvals

## A TESTED AND PROVEN SUCCESS RATE

- Infiltrator is the leading manufacturer of products for onsite wastewater treatment systems in North America.
- Millions of Infiltrator onsite wastewater drainfield systems have been installed worldwide.
- Beginning in 1987, Infiltrator products have stood the test of time with an established history of performance and reliability.

## PRODUCT AVAILABILITY

Infiltrator has an extensive network of distributors throughout North America. These knowledgeable professionals maintain local inventories of our products and also provide contractors with product delivery and installation support. Plus, Infiltrator has a dedicated and experienced team of sales, customer service, and technical assistance professionals who are focused on the wastewater industry.

## RESPONSIVE SERVICE

- Our technical staff and area sales representatives maintain a strong presence where it counts – in the field.
- Contractor, designer and engineer training and certification classes are available.
- We offer field demonstrations to help educate contractors and regulators.
- Product brochures, installation manuals, videos, and state- and province-specific design tools are available on our website or by calling our technical service team.

## Contents

### Tanks

Infiltrator Tanks .....	2, 3
Potable Tanks.....	4
GIT-Tanks.....	4

### Tank Risers

EZsnap Risers.....	5
Infiltrator Guardian .....	5
Safety Star.....	5

### Drainfield

Quick4 Chambers .....	6
Quick5 Chambers .....	7
Quick4 Plus Chambers .....	8
Arc Chambers.....	10
EZflow.....	12

### Combined Treatment and Dispersal

Advanced Enviro Septic (AES).....	14
AeroFin .....	15
Advanced Treatment Leachfield (ATL) .....	15

### Pump Controllers

Aquaworx.....	16
Aquaworx MARC .....	16
Aquaworx Tapper .....	16
Aquaworx Transducer .....	16
Aquaworx Remediator .....	17

### Advanced Treatment

ECOPOD-Edge .....	18
ECOPOD-NX.....	18
ECOPOD-N.....	19
ENVIRO-AIRE .....	19
ECOPOD Treatment Plant.....	20
ENVIRO-AIRE Treatment Plant .....	20

[infiltratorwater.com](http://infiltratorwater.com)



# Infiltrator Tanks

The strength and versatility of Infiltrator septic tanks enable a wide-range of installation possibilities, including shallow installations and multiple and serial tank configurations. Infiltrator's lightweight construction allows for easy storage and delivery, and offers the quickest installation in the onsite wastewater industry.

The engineered mid-seam joint accepts a continuous loop EPDM gasket. Infiltrator's EPDM gasket design utilizes technology and materials from the sanitary sewer pipe industry to deliver a reliable watertight seal. The two-piece tank body is permanently aligned and fastened using an integrated system of high-strength plastic alignment dowels and locking seam clips. The tank does not require water filling during installation and can be pumped dry during pump-outs.





**Infiltrator's chambers, septic tanks and EZflow drainfield products are manufactured in the USA from 95% recycled plastics.**

## Benefits

- Lightweight plastic construction and inboard lifting lugs allow for easy delivery and handling
- Structurally reinforced access ports eliminate distortion during installation and pump-outs
- Reinforced structural ribbing and fiberglass bulkheads offer additional strength
- Can be pumped dry during pump-outs (no need to refill with water)
- Suitable for use as a septic tank, trash tank, pump tank, or rainwater (non-potable) tank, in-series or multiple serial tank configurations

**All Infiltrator septic tanks are fully assembled and available through our distribution network.**

## CM-1060 TANK CUTAWAY





# IM-Tank CM-Tank



IM-300 Pump Tank	
<b>Part Number:</b> (No Plumbing)	IM300P/1/0
<b>Part Number:</b> (Plumbing)	IM300P/1/P
<b>Size:</b>	51"W x 51"L x 51"H (1293 mm x 1293 mm x 1283 mm)
<b>Working Capacity:</b>	278 gal (1052 L)
<b>Total Capacity:</b>	322 gal (1219 L)

**The quickest installation  
in the onsite industry**

**Installed with 6" to 48" of cover**  
\* 52" cover for the IM-300

**Shallow installations and  
multiple and serial tank  
configurations**

**300 to 1500 gallon capacity**

IM-540 Septic/Pump Tank	
<b>Part Number:</b> (No Plumbing)	IM540P/1/0
<b>Part Number:</b> (Plumbing)	IM540P/1/P
<b>Size:</b>	62"W x 65"L x 55"H (1567 mm x 1648 mm x 1387 mm)
<b>Working Capacity:</b>	475 gal (1798 L)
<b>Total Capacity:</b>	552 gal (2090 L)



CM-1060 Septic/Pump Tank	
<b>Part Number</b> (Plumbing, One Compartment)	CM1060P/1/P
<b>Part Number</b> (Plumbing, Two Compartment)	CM1060P/2/P
<b>Part Number</b> (No Plumbing, One Compartment)	CM1060P/1/0
<b>Part Number</b> (No Plumbing, Two Compartment)	CM1060P/2/0
<b>Size:</b>	62"W x 134"L x 55"H (1567 mm x 3409 mm x 1384 mm)
<b>Working Capacity:</b>	1111 gal (4207 L)
<b>Total Capacity:</b>	1309 gal (4956 L)

IM-1250 Septic Tank	
<b>Part Number</b> (Plumbing, One Compartment)	IM1250P/1/P
<b>Part Number</b> (Plumbing, Two Compartment)	IM1250P/2/P
<b>Part Number</b> (No Plumbing, One Compartment)	IM1250P/1/0
<b>Part Number</b> (No Plumbing, Two Compartment)	IM1250P/2/0
<b>Size:</b>	62"W x 154"L x 55"H (1567 mm x 3911 mm x 1387 mm)
<b>Working Capacity:</b>	1278 gal (4839 L)
<b>Total Capacity:</b>	1480 gal (5602 L)

IM-1530 Septic Tank	
<b>Part Number</b> (Plumbing, One Compartment)	IM1530P/1/P
<b>Part Number</b> (Plumbing, Two Compartment)	IM1530P/2/P
<b>Part Number</b> (No Plumbing, One Compartment)	IM1530P/1/0
<b>Part Number</b> (No Plumbing, Two Compartment)	IM1530P/2/0
<b>Size:</b>	62"W x 176"L x 55"H (1567 mm x 4460 mm x 1384 mm)
<b>Working Capacity:</b>	1537 gal (5818 L)
<b>Total Capacity:</b>	1787 gal (6765 L)

# IM-Tank Potable Water

The Infiltrator IM-Series potable water and rainwater harvesting tanks are lightweight, strong and durable. These potable, watertight cisterns are offered with Infiltrator's potable heavy-duty lids. Infiltrator injection-molded tanks provide a revolutionary improvement in plastic tank design, offering long-term strength and watertightness.



## Infiltrator IM-Potable Water Tank Series

Parameter	IM-550C	IM-1280C	IM-1760C
Part No. (No Plumbing)	IM550C/1/0	IM1280C/1/0	IM1760C/1/0
Part No. (Plumbing)	IM550C/1/P	IM1280C/1/P	IM1760C/1/P
Total Capacity	552 gal (2090 L)	1287 gal (4872 L)	1787 gal (6764 L)
Length	65" (1651 mm)	127" (3229 mm)	176" (4470 mm)
Width	62" (1575 mm)	62" (1575 mm)	62" (1575 mm)
Height	55" (1397 mm)	55" (1397 mm)	55" (1397 mm)
Fiberglass Supports	0	2	4
Maximum Pipe Diameter	4" (102 mm)	6" (152 mm)	4" (102 mm)

## Benefits

- Lightweight plastic construction and inboard lifting lugs allow for easy delivery and handling
- Suitable for use as a potable pump tank, rainwater harvesting or water storage tank

# GIT-Series Grease Interceptor

GIT-Series offer models in gravity grease and hydromechanical interceptors. Designed for easy installation, non-corrosive, fiberglass embedded, polypropylene improves durability. A durable solids-tight baffle creates a two-compartment solution that prevents fats, oils and grease (FOG) from short-circuiting across the interceptor. Traffic installations (AASHTO H20 rated) achievable with the use of a steel reinforced concrete slab, Infiltrator's Pipe Adaptor Ring, dual wall corrugated pipe (by other), and Infiltrator's cast iron lid.



## Grease Interceptor Tank Series

Parameter	GIT-540	GIT-1060	GIT-1530
Part No.	GIT540P/2/P	GIT1060P/2/P	GIT1530P/2/P
Part No. (Assembled)	GIT540A/2/P	GIT1060A/2/P	GIT1530A/2/P
FOG Capacity	413 gal (3011 lbs)	139 gal (1014 lbs)	192 gal (1400 lbs)
Length	65" (1648 mm)	134" (3409 mm)	176" (4460 mm)
Width	62" (1575 mm)	62" (1567 mm)	62" (1575 mm)
Height	55" (1397 mm)	55" (1397 mm)	55" (1397 mm)
Max. Traffic Burial Depth	48" (1219 mm)	48" (1219 mm)	48" (1219 mm)
Min. Traffic Burial Depth	18" (457 mm)	18" (457 mm)	18" (457 mm)
Maximum Pipe Diameter	4" (102 mm)	4" (102 mm)	4" (102 mm)

## Benefits


- Molded using a non-corrosive, fiberglass-embedded polypropylene for greater durability
- Delivery and handling made quick with the lightweight thermoplastic design
- Low profile design using structural corrugations and fiberglass support posts achieve optimal below-grade installation

# EZsnap® Risers

The EZsnap riser is designed to create an easy-to-assemble watertight riser system for septic tanks, pump tanks, and cisterns. The EZsnap riser features click and lock technology, eliminating the need for assembly tools, sealant/caulk and hardware.

Available in black or green with 2", 6" and 12" tall sections.

EZsnap 24" Riser System		
Item	Part Number (Green/Black)	Dimensions
24" Riser Lid	IMLID-2400 IMLID-B2400	30" x 30" x 2.75" (762 mm x 762 mm x 70 mm)
Pipe Adapter Ring	SNAPPAR-2400-2	27.75" x 27.75" x 3.5" (705 mm x 705 mm x 89 mm)
24" x 2" Riser	SNAPRIS-2402 SNAPRIS-B2402	27.75" x 27.75" x 3" (705 mm x 705 mm x 76 mm)
24" x 6" Riser	SNAPRIS-2406 SNAPRIS-B2406	27.75" x 27.75" x 7" (705 mm x 705 mm x 178 mm)
24" x 12" Riser	SNAPRIS-2412 SNAPRIS-B2412	27.75" x 27.75" x 13" (705 mm x 705 mm x 330 mm)
24" Safety Star	SNAPSAFT-2400	26.5" x 26.5" x 3.5" (673 mm x 673 mm x 89 mm)



Stackable for efficient shipping and storage

## Infiltrator Guardian™ 24-inch Safety Device

Strong secondary level of protection to prevent accidental fall or entry into a tank.



### Child-Safe Design

Integrated spring-loaded latch automatically engages every time the gate is closed, requiring 50 pounds of force to open it.



### Easy Access

The gate design allows waste haulers quick access to the tank below with 22.5 inches of space to navigate hose.



### Benefits

- Capable of supporting over 300 pounds
- Compatible with Infiltrator EZsnap & EZset (24-inch diameter) riser systems and lids, corrugated dual-wall and ultra-rib pipe
- Easily navigate a vacuum hose throughout the tank's riser
- A single stainless-steel screw locks the safety gate in place

# Quick4<sup>®</sup> Chambers

- Four-foot chamber lengths are easy to handle and install
- Supports wheel loads of 16,000 lbs/axle with 12" of cover



- Quick4 Standard
- Quick4 High Capacity
- Quick4 Equalizer 36
- Quick4 Equalizer 24 Low Profile
- Quick4 Equalizer 24
- Quick4 Equalizer 24 Heavy Duty

Quick4 Standard Chamber		Part Numbers: Q4STD/ Q4STDE	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 53"L x 12"H (864 mm x 1346 mm x 305 mm)		
<b>Effective Length:</b>	48" (1219 mm)		
<b>Multiport Endcap:</b>	Eight molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	34"W x 16"L x 12"H (864 mm x 406 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	26.4" (671 mm)	<b>Invert Height:</b>	8" (203 mm)



Quick4 High Capacity Chamber		Part Numbers: Q4HC/Q4HCE	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 53"L x 16"H (864 mm x 1346 mm x 406 mm)		
<b>Effective Length:</b>	48" (1219 mm)		
<b>Multiport Endcap:</b>	Eight molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	34"W x 19"L x 16"H (864 mm x 483 mm x 406 mm)		
<b>Additional Length per Pair of Endcaps:</b>	28.8" (732 mm)	<b>Invert Height:</b>	11.5" (292 mm)



Quick4 Equalizer 36 Chamber		Part Numbers: Q4EQ36/Q4EQ36E	
<b>Application:</b>	24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	22"W x 53"L x 12"H (559 mm x 1346 mm x 305 mm)		
<b>Effective Length:</b>	48" (1219 mm)		
<b>Multiport Endcap:</b>	Six molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	22"W x 16"L x 12"H (559 mm x 406 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	25.2" (640 mm)	<b>Invert Height:</b>	6" (152 mm)



## Features

- Contour Swivel Connection™ allows the chamber to swivel up to 15°, right or left
- Higher long-term acceptance rate (LTAR) – a reliable top-performing system
- Smaller footprint with equal or better performance allows less site disruption
- Louvered sidewalls for maximum infiltration
- Low profile chambers for shallow placement applications

**Multiport Endcaps**  
Molded-in  
inlets/outlets allow  
for piping flexibility

Quick4 Equalizer 24 Chamber and Equalizer 24 Heavy Duty (HD) Chamber		Part Numbers: Q4EQ24/Q4EQ24E Part Numbers: Q4EQ24HD/Q4EQ24E	
<b>Application:</b>	18" or 24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	16"W x 53"L x 11"H (406 mm x 1346 mm x 279 mm)		
<b>Effective Length:</b>	48" (1219 mm)		
<b>Multiport Endcap:</b>	Six molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	16"W x 14"L x 12"H (406 mm x 356 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	22.8" (579 mm)	<b>Invert Height:</b>	6" (152 mm)



Quick4 Equalizer 24 Low Profile Chamber		Part Numbers: Q4EQ24LP / Q4EQ24LPE	
<b>Application:</b>	18" or 24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	16"W x 53"L x 8"H (406 mm x 1346 mm x 203 mm)		
<b>Effective Length:</b>	48" (1219 mm)		
<b>Endcap:</b>	Offers a simple overlap design for easy installation.		
<b>Size:</b>	14"W x 7"L x 8"H (356 mm x 178 mm x 203 mm)		
<b>Additional Length per Pair of Endcaps:</b>	9" (229 mm)	<b>Invert Height:</b>	2" (51 mm)



# Quick5<sup>®</sup> Chambers

- Five-foot chamber lengths are easy to handle and install
- Supports wheel loads of 16,000 lbs/axle with 12" of cover

Quick5 Standard Chamber		Part Numbers: Q5STD/Q4STDE	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 65"L x 12"H (864 mm x 1651 mm x 305 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Multiport Endcap:</b>	8-molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	34"W x 16"L x 12"H (864 mm x 406 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	26.4" (671 mm)	<b>Invert Height:</b>	8" (203 mm)



Quick5 Equalizer 36 Chamber		Q5EQ36/Q4EQ36E	
<b>Application:</b>	24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	22"W x 65"L x 12"H (559 mm x 1651 mm x 305 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Multiport Endcap:</b>	Six molded-in high and low inlets for maximum piping flexibility.		
<b>Size:</b>	22"W x 16"L x 12"H (559 mm x 406 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	28.8" (732 mm)	<b>Invert Height:</b>	11.5" (292 mm)



Quick5 Standard  
Quick5 Equalizer 36

# Quick4Plus<sup>®</sup>

## Chambers

Infiltrator chambers give designers, installers and owners greater flexibility in the placement of the septic drainfield.

- Four-foot chamber lengths are easy to handle and install
- Supports wheel loads of 16,000 lbs/axle with 12" of cover

### Quick4 Plus Standard

### Quick4 Plus High Capacity

Quick4 Plus Standard Chamber		Part Number: Q4+STD
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds	
<b>Size:</b>	34"W x 53"L x 12"H (864 mm x 1346 mm x 305 mm)	
<b>Effective Length:</b>	48" (1219 mm)	
<b>Endcap:</b>	Quick4 Plus All-in-One 12	

Quick4 Plus High Capacity Chamber		Part Number: Q4+HC
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds	
<b>Size:</b>	34"W x 53"L x 14"H (864 mm x 1346 mm x 356 mm)	
<b>Effective Length:</b>	48" (1219 mm)	
<b>Endcap:</b>	Quick4 Plus All-in-One 12	

Quick4 Plus All-in-One 12 Endcap		Part Number: Q4+A112E
<b>Application:</b>	Use at either end of a chamber row for an inlet/outlet or can be installed mid-trench. Side, end or top inletting. Compatible with Quick4 Plus Standard and Quick4 Plus High Capacity Chambers.	
<b>Size:</b>	34"W x 20.5"L x 13"H (864 mm x 520 mm x 330 mm)	
<b>Additional Length per Pair of Endcaps:</b>	37" (940 mm)	<b>Additional Length when used midline:</b> 11.4" (290 mm)
<b>Invert Height:</b>	5.3", 8" (134 mm, 203 mm)	<b>Optional Accessory:</b> All-in-One Periscope

Quick4 Plus All-in-One Periscope		Part Number: Q4+P
<b>Application:</b>	Allows for raised, invert installations with 180° directional inletting. All-in-One 8 Endcap: 9" raised invert. All-in-One 12 Endcap: 13" invert.	
<b>Size:</b>	5"W x 9"L x 6"H (127 mm x 229 mm x 152 mm)	
<b>Invert Height:</b>	9", 13" (229 mm, 330 mm)	



## Quick4 Plus Standard Low Profile Quick4 Plus Equalizer 36 Low Profile

Added Strength Through  
Center Structural Columns

Quick4 Plus Standard Low Profile (LP) Chamber		Part Number: Q4+STDLP
<b>Application</b>	Reduced height applications, 4" shorter than standard chambers. 36" wide trench, curved, straight or side by side in beds	
<b>Size</b>	34"W x 53"L x 8"H (864 mm x 1346 mm x 203 mm)	
<b>Effective Length</b>	48" (1219 mm)	
<b>Endcap</b>	Quick4 Plus All-in-One 8 or Quick4 Plus	



Quick4 Plus Equalizer 36 Low Profile (LP) Chamber		Part Number: Q4+EQ36LP
<b>Application</b>	Reduced height applications, 4" shorter than standard chambers. 24" wide trench, curved, straight or side by side in beds	
<b>Size</b>	22"W x 53"L x 8"H (559 mm x 1346 mm x 203 mm)	
<b>Effective Length</b>	48" (1219 mm)	
<b>Endcap</b>	Quick4 Plus All-in-One 8 or Quick4 Plus	



Quick4 Plus All-in-One 8 Endcap		Part Number: Q4+A1E		
<b>Application:</b>	Use at either end of a chamber row for an inlet/outlet or can be installed mid-trench. Side, end or top inletting. Compatible with Quick4 Plus Low Profile Chambers.			
<b>Size:</b>	18"W x 13"L x 8"H (457 mm x 330 mm x 203 mm)			
<b>Additional Length per Endcap:</b>	10.4" (264 mm)	<b>Invert Height:</b>	3.3" (84 mm)	<b>Optional Accessory:</b> All-in-One Periscope



Quick4 Plus Endcap		Part Number: Q4+E		
<b>Application:</b>	Simple, flat design that allows for a pipe installation at the end of the chamber row. Piping drill points are set for gravity or pressure pipe. Compatible with Quick4 Plus Low Profile Chambers.			
<b>Size:</b>	18"W x 7"L x 8"H (457 mm x 178 mm x 203 mm)			
<b>Additional Length per Endcap:</b>	4.5" (114 mm)	<b>Invert Height:</b>	3.3" (84 mm)	



Low profile chambers are ideal for shallow applications.

# Arc<sup>®</sup> Chambers

Arc 18 • Arc 24 • Arc 36  
Arc 36 LP • Arc 36 HC  
Arc Side Port Coupler

Diamond plate texture increases slip resistance and enhances ease of installation.



## Features


- Injection-molded from polyolefin for lightweight and sturdy design
- 20-degree integral articulating joint that is ideal for either straight or contoured septic drainfield applications
- Designed to accommodate both gravity-fed and pressure-dosed systems
- Corrugated chamber design eliminates flat surfaces and provides increased load bearing capability in the trench
- "Lock and Drop" joint provides a positive connection during installation and backfill
- The inlet/outlet endcap is universal
- Convenient five-foot lengths are easy to handle
- Increased plumbing option with Side Port Coupler component which snaps in place to allow side entry at any joint throughout trench line

## Chamber Requirements

Infiltrator's chambers meet the load rating of H-10 (16,000 lb per axle) with a minimum of 12 inches of cover when tested in accordance with IAPMO PS 63\* and installed in accordance with manufacturer's installation procedures.

*\* Excludes Arc 36 Low Profile*

## Typical Arc Trench Cross Section



Arc 18 Chamber		Part Numbers: 1812BD-PP/1802BD	
<b>Application:</b>	18 or 24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	16"W x 67"L x 11"H (406 mm x 1702 mm x 279 mm)		
<b>Effective Length:</b>	60" (1524 mm)	<b>Invert Height:</b>	6" (152 mm)



Arc 24 Chamber		Part Numbers: 2412BD3/2402BD	
<b>Application:</b>	24" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	22"W x 67"L x 12"H (559 mm x 1702 mm x 305 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Side Port Coupler:</b> five molded-in high and low inlets for mid-trench piping flexibility.			
<b>Size:</b>	22"W x 9"L x 12"H (559 mm x 229 mm x 305 mm)		
<b>Additional Length per Pair of Endcaps:</b>	12" (305 mm)	<b>Invert Height:</b>	6.25" (159 mm)



Arc 24 Side Port Coupler



Arc 36 Chamber		Part Numbers: 3613BD3-PP/3603BD3	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 63"L x 13"H (864 mm x 1600 mm x 330 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Side Port Coupler:</b> five molded-in high and low inlets for mid-trench piping flexibility.			
<b>Size:</b>	34"W x 17"L x 13"H (864 mm x 432 mm x 330 mm)		
<b>Additional Length per Pair of Endcaps:</b>	14" (356 mm)	<b>Invert Height:</b>	7.25" (184 mm)



Arc 36 Side Port Coupler



Arc 36 LP Chamber		Part Numbers: 3608BD PP/3624LPEC	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 64"L x 8"H (864 mm x 1626 mm x 203 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Invert Height:</b>	3.8" (197 mm)		



Arc 36 High Capacity Chamber		Part Numbers: 3616BD3 PP/3606BD2	
<b>Application:</b>	36" wide trench, curved, straight or side by side in beds		
<b>Size:</b>	34"W x 63"L x 16"H (864 mm x 1600 mm x 406 mm)		
<b>Effective Length:</b>	60" (1524 mm)		
<b>Side Port Coupler:</b> five molded-in high and low inlets for mid-trench piping flexibility.			
<b>Size:</b>	34"W x 17"L x 16"H (864 mm x 432 mm x 406 mm)		
<b>Additional Length per Pair of Endcaps:</b>	14" (356 mm)	<b>Invert Height:</b>	10.5" (267 mm)



Arc 36 HC Side Port Coupler



## Side Port Coupler

Each Arc chamber model has an accompanying accessory called the Side Port Coupler (SPC). The SPC component snaps in place to allow additional pivoting space when used mid-line. The SPC offers flexibility of pivoting when installed in series between two chambers within the chamber line to allow for increased turning capability.


# EZflow<sup>®</sup> Septic

EZflow is an environmentally friendly replacement for stone and pipe in septic drainfields using an engineered geosynthetic aggregate modular design.

EZflow is certified by IAPMO and the ICC-ES PMG Listing Program.

An EZflow system is designed to improve infiltrative performance by eliminating fines and reducing compaction and embedment associated with crushed stone. Pre-assembled units include a 4" perforated pipe surrounded by aggregate covered in geotextile and held in place with a durable high-strength netting. Available in easy-to-contour 5' and 10' lengths in diameters of 7", 8", 9", 10", 12", 13", 14" or 18".

## Geosynthetic aggregate is free of fines



**Lightweight expanded polystyrene** construction offers structural integrity and resists compaction. Engineered flow channels increase void space creating improved water flow and greater effluent storage. Extended geotextile barrier eliminates intrusion through unprotected surfaces.

## Benefits



- Always clean and free of fines
- Bundles are quick to install, using simple snap internal couplers, saving costs on heavy machinery and labor
- Modular construction allows configurations to match trench dimensions for most system configurations
- Engineered for optimal effluent storage and absorption efficiencies
- Ability to contour along sloped sites and around trees or landscaping
- Lightweight, 5' or 10' lengths are perfect for repairs and tight job sites
- Easier cleanup at job site with the elimination of stone
- Manufactured from recycled materials rather than mined natural resources

### EZflow Bundles for Septic Applications

	Single Bundle System	Two Bundle System	Three Bundle System	Four Bundle System
<b>Diameter</b>				
10"	1001-P-GEO 1001-P	1002-GEO-SEP	1003-GEO-SEP 1003-SEP	-
12"	1201-P-GEO 1201-A-GEO	1202-GEO-SEP	1203-GEO-SEP 1203-SEP	1204-GEO-SEP
13"	-	-	1303-GEO-SEP	-
14"	1401-P-GEO	-	-	-
18"	1801-P-GEO	-	-	-

P = Pipe (Corrugated Polyethylene Pipe ASTM F667)  
A = Aggregate only bundle

GEO = Geotextile Integrated  
SEP = Septic Configuration











Lightweight expanded polystyrene aggregate offers structural integrity and resists compaction

### Benefits

- Convenient 10' long sections are easy to connect using internal couplers
- EZflow products can be easily transported and installed by a single worker, dramatically reducing labor costs
- Superior flow rate when compared to gravel due to lack of fines
- EZflow drainage systems have high storage capacity created by the engineered flow channels in the aggregate
- EZflow's aggregate-pipe combination and aggregate-only bundles can easily bend around corners and other obstacles to conform to your project's needs
- Using EZflow recycled polystyrene aggregate prevents millions of pounds of plastic waste from entering landfills

### EZflow Bundles for Drainage Applications

7" Bundles		10" Bundles		15" Bundles	
Part #	Description	Part #	Description	Part #	Description
701-A-MESH	 7" Diameter	1001-A-MESH	 10" Diameter	1501-A-MESH	 15" Diameter
701-F-MESH	 7" Diameter with 3" Pipe in Center	1001-FC-MESH	 10" Diameter with 4" Pipe in Center	1501-FC-MESH	 15" Diameter with 6" Pipe in Center
		1001-FB-MESH	 10" Diameter with 4" Pipe at Bottom	1501-B-MESH	 15" Diameter with 6" Pipe at Bottom

# Advanced Enviro-Septic®



## PASSIVE ONSITE WASTEWATER TREATMENT SYSTEMS

Advanced Enviro-Septic® (AES) passively creates a powerful biological ecosystem that continually digests organic matter in wastewater. Along with other patented components, AES also features the Bio-Accelerator® fabric, which speeds the development of the biomat and allows for distribution of wastewater along the entire length of the pipes. The AES treatment system has been proven to remove up to 99% of wastewater impurities without the need for electricity or replacement media.

Testing in accordance with NSF/ANSI 40 has determined that the AES system is capable of treating domestic strength wastewater to Class I levels.

### Features

- Treats and disperses wastewater in the same footprint
- No electricity, replacement media or additional maintenance required
- Flexible configurations for sloped or curved sites
- Can be used in traffic rated H20 configurations

Combined treatment and dispersal (CTD) systems are non-mechanical, non-biodegradable, low long-term life cycle cost systems for residential, commercial, and community onsite wastewater treatment system designs. Infiltrator's combined treatment and dispersal (CTD) products offer a high level of treatment in a small footprint.

Advanced Enviro-Septic (AES)		
Item	Part Number	Dimensions
Advanced Enviro-Septic Pipe Unit 10'	AES Unit	120" x 12" x 12" (3048 mm x 305 mm x 305 mm)
Enviro-Septic Pipe 10'	ESP-UNIT	120" x 12" x 12" (3048 mm x 305 mm x 305 mm)
Enviro-Septic Coupling	ESC-2	7" x 12" x 12" (178 mm x 305 mm x 305 mm)
Enviro-Septic Offset	ESO	5" x 12" x 12" (127 mm x 305 mm x 305 mm)
Endccap	ESE	5" x 12" x 12" (127 mm x 305 mm x 305 mm)

NSF Testing Parameters	AES Test Results
BOD <25 mg/L	8 mg/L
TSS <30 mg/L	4 mg/L



# AeroFin™


An effective solution for compact lots and sites with footprint constraints. Demonstrated to the removal of up to 99% of wastewater impurities.



AeroFin		
Item	Part Number	Dimensions
AeroFin Unit	AF08	98" x 2.25" x 12.75" (2489 mm x 57 mm x 324 mm)
AeroFin Manifold	AFM	17.75" x 7.88" x 14.50" (451 mm x 200 mm x 368 mm)
AeroFin Cap	AFEC	3.75" x 2.50" x 13.13" (95 mm x 63 mm x 333 mm)
AeroFin Install Tool	AFIT	38" x 24" x .25" (965 mm x 616 mm x 6 mm)

## Features

- Testing in accordance with NSF/ANSI 40 has determined that the AeroFin system is capable of treating domestic strength wastewater to Class I levels
- Treats and disperses wastewater in the same footprint
- No electricity, replacement media or additional maintenance



# ATL™



A passive advanced treatment leachfield system designed as an environmentally friendly alternative to stone and pipe drainfields, the ATL system is a sand-lined combined treatment and dispersal leachfield system.

ATL by Infiltrator		
Item	Part Number	Dimensions
ATL 10' Length	ATL-010	120" x 12" x 12" (3048 mm x 305 mm x 305 mm)
4" Coupler-Internal	AC-COUPLER-4	4" x 8" x 4" (102 mm x 203 mm x 102 mm)
Corrugated Pipe Adapter 4"	AC-IT44CC	4" x 8" x 4" (102 mm x 203 mm x 102 mm)
4" Plug Internal	AC-PLUG-4	4" x 3" x 4" (102 mm x 76 mm x 102 mm)

## Features

- Testing in accordance with NSF/ANSI 40 has determined that the ATL system is capable of treating domestic strength wastewater to Class I levels
- Passive treatment system, no moving parts or power
- Passive treatment system, no moving parts or power
- Modules are quick and easy to install
- Shallow system maximizes site suitability and reduces amount of sand fill required
- No venting and sand cover requirements

# Aquaworx

The Aquaworx Intelligent Pump Control panel provides an innovative approach to pump con-

## Benefits

- Simplified wiring for easy installation
- Unique user interface with Mountable and Removable Controller (MARC™)
- Data logging provides easy access to historical data
- Accurate timings eliminates need for a stopwatch
- Liquid level displayed for draw-downs means no tape measure required
- Veto level override function allows different timing at different loads
- Manual / Off / Auto Operation
- Audible alarm with push to silence
- Floatless pressure transducer in the pump chamber

## Simplex Control Panel Part Number IPC-S01

Designed specifically for the onsite industry, the IPC Panel leverages simple pressure transducer technology for the enhancement of pump system performance and ease of installation. Relying on an embedded microprocessor in the pump controller and a floatless pressure transducer in the pump chamber, the IPC Panel monitors liquid levels, controls pumping time intervals, and logs events in real-time.



## The MARC™ Part Number MAR-04

The IPC Panel utilizes the MARC™ to operate and collect system data. The MARC is a user friendly interface to monitor and operate the IPC panels.



## The Tapper Part Number TAPR-01

The Tapper broadcasts a wireless signal that is specifically designed to allow the user to program the Aquaworx IPC Panel using a Wi-Fi enabled device. The Tapper connects to the panel using a standard RJ45 cable (included) and communicates via a Wi-Fi connection to a Wi-Fi enabled device such as a mobile phone, tablet or laptop computer. Once connected, the user navigates to a website that has all control settings for the IPC Panel. The Tapper is intended for use with multiple panels and includes a USB slot, allowing the user to capture and download system events and settings onto a removable USB memory device.

## The Transducer Part Number TRN-40, TRN-80, TRN-120

The Aquaworx Transducer Assembly connects to the panel with a wire cable, making it easier to wire and more cost effective than a float system. With most mechanical systems, floats trigger the timer and alarms at specific liquid levels. For each level, a function and float are required, and typically three to five floats are installed. Aquaworx utilizes a Transducer Assembly that controls multiple functions, providing the data necessary to perform system functions.



# Aquaworx Remediator



## Rejuvenate a Failing Drainfield

### Remediator

Part Number P40: RKT-03

Part Number P80: RKT-02

The Aquaworx Remediator is a simple, easy-to-install septic system remediation technology that rejuvenates a failing drainfield with minimal landscape disruption. The unique system is inserted into an existing septic tank of a malfunctioning system and reverses the drainfield clogging process.



### A Proven Track Record

More than 7,000 malfunctioning septic systems have been restored to normal operation with this bioremediation technology. The Aquaworx Remediator is a technology that is accepted or approved as a septic system repair by numerous regulatory agencies.



### Benefits

- Eliminate the need for a complete drainfield replacement and the resulting landscape damage caused by heavy equipment
- Problems associated with a malfunctioning septic system like odors and wet areas in the yard are eliminated in as little as two weeks
- Environmental solution that strengthens the natural process of wastewater treatment and groundwater recharge
- Easy installation with no heavy equipment allows for minimal disruption and quick return on investment
- Permanent, non-invasive solution with minimal cost to operate and maintain

### Aquaworx Remediator

<b>Column Diameter at Base:</b>	15" (381 mm)
<b>Total Height:</b>	30" (762 mm)
<b>Weight:</b>	38 lbs (17 kg)
<b>Flow Rate:</b>	600 gal/day (2271 L) for a 4 bedroom house
<b>Air Pump Weight:</b>	13 lbs (6 kg)
<b>Air Pump Dimensions:</b>	6.8"W x 8.2"L x 7.5"H (173 mm x 208 mm x 191 mm)

# ECOPOD®-Edge

## Nitrification and Denitrification Occur in a Single Tank



Certified to NSF/ANSI Standards 40 & 245



**79%** Total Nitrogen Reduction

## NSF/ANSI 40 AND 245 CERTIFIED RESIDENTIAL WASTEWATER

The ECOPOD-Edge is the next generation in fixed film wastewater treatment technology, engineered to deliver exceptional treatment performance with a smaller system footprint and minimal maintenance. Certified under NSF/ANSI Standard 40 and 245, it produces an average effluent quality of 9 mg/L CBOD, 8 mg/L TSS, and 11 mg/L Total Nitrogen (79% reduction). The system features “Edge Zone” technology that forms anoxic subzones within the aerobic chamber to support continuous biological nutrient removal.

### Benefits

- Significantly reduces CBOD, TSS, and Total Nitrogen to help protect groundwater and surface water
- Compact 500 GPD model fits in a 1000-gallon Infiltrator CM-1060 tank for a reduced footprint
- Fixed film process offers stable, robust treatment under continuous or intermittent use
- Simple to assemble and install for efficient jobsite workflows
- No internal mechanical parts for ease of maintenance

# ECOPOD-NX®

The ECOPOD-NX is a recirculating moving bed bioreactor designed to treat residential wastewater. It utilizes fully submerged media and an air lift to facilitate recirculation that promotes greater denitrification. The design has been certified to NSF/ANSI 40 and 245 with average effluent quality of 7 mg/L BOD and 7 mg/L TSS.



Certified to NSF/ANSI Standards 40 & 245



### Benefits

- For one and two tank configurations.
- Easy to transport and install single tank configuration
- Designed specifically to minimize sludge production for lower long-term maintenance

# ECOPOD-N<sup>®</sup>

## NSF/ANSI 40 AND 245 Residential Wastewater Treatment System


ECOPOD-N is the clear choice for an onsite wastewater disposal system where nitrogen reduction is required. It has been tested under Standard 40 and 245 of NSF/ANSI with an average nitrogen reduction of greater than 50% and met and exceeded Class 1 requirements with an average effluent quality of 9 mg/L BOD5 and 8 mg/L TSS.



Units are available from 500 gpd to 1,500 gpd

### Benefits

- The fixed film process provides a robust solution suitable for continuous or intermittent use
- Flexible and easy installations in any septic tank
- With no mechanical parts internal to the unit, the ECOPOD is easy to maintain



# ENVIRO-AIRE<sup>™</sup>

ENVIRO-AIRE treatment units utilize long-standing wastewater treatment technology and scale it to residential daily flow rates. The design has been certified to NSF/ANSI 40 with average effluent quality of 12 mg/L BOD and 16 mg/L TSS.




Certified to NSF/ANSI Standard 40

For flows up to 750 gpd.

### Benefits

- Industry proven solution with NSF/ANSI 40 certification
- Flexible and easy installations in a single Infiltrator tank
- No mechanical parts, easy to maintain
- Low life cycle costs resulting from efficient design with minimal maintenance requirements




Adding the ENVIRO-AIRE treatment unit to an onsite system provides a three-step process to treat incoming wastewater resulting in highly treated effluent suitable for a variety of disposal methods and challenging site conditions.

# ECOPOD Treatment Plant

**ECOPOD Treatment Plants are designed to convert flows of 1,500 to 250,000 gallons per day into clear and odor-free treated effluent.**

The ECOPOD treatment plants are custom designed to the particular needs of each project. Suitable for permanent or temporary use in areas outside municipal wastewater systems, each treatment plant is custom-built at the factory and shipped to the treatment plant project site.

Secondary and tertiary treatment systems include aeration, settling, filters, clear well chambers, disinfection methods and other ancillary equipment such as blowers, pumps, electrical controls, aeration equipment, filter media and liquid level sensors. Other items, such as gratings, handrails, stairways and flow measuring equipment can be provided. An Infiltrator representative can assist you in specifying the system that will meet your requirements.



## TYPICAL APPLICATIONS


Convenience Store • Restaurant/Bar • RV Park • School • Subdivision • Mixed Commercial Campground  
Factory • Hotel/Resort • Apartments/Condos • Commercial • Event/Conference Venue • Mobile Home  
Park Religious Facility • State/National Park • Alcoholic Beverage Production • Government/Military  
Mixed Residential • Assisted Living • Butchery Man Camp • Power Plant • Public Open Space

# ENVIRO-AIRE™ Treatment Plant

**Advanced Wastewater Treatment System  
Extended Aeration 1,500 to 250,000 GPD**

**The Clear Wastewater Treatment  
Solution for Remote Locations**

Suitable for permanent or temporary use in areas outside municipal wastewater systems, each ENVIRO-AIRE treatment plant is custom built at the factory and shipped to the project site as a self-contained unit that requires only minimal field work. These extended aeration plants can be as simple as secondary treatment or as complex as a system for biological nutrient reduction.



# ENGINEERED. RELIABLE. READY.

Everything You Need for a Wastewater System, Orenco Has It.



Orenco designs and manufactures thousands of innovative products for on-site and decentralized wastewater collection and treatment systems. These products are engineered by experts to be strong, durable, reliable, and competitively priced. They're perfect for residential and commercial properties, small or large flows, household or high-strength waste, even in poor soils or high groundwater.

Whether you're looking for a single item or a complete system package, we've got you covered with ...



- **Gravity and Pumping Products:** including Biotube® pump vaults, effluent filters, and complete pump packages.
- **Collection Systems:** like Prelos® and ProSTEP for efficient community solutions.
- **Advanced Secondary Treatment:** featuring AdvanTex® and MBBR systems for superior performance.
- **Control Panels:** for any application.

**Ready to Explore Our Full Product Line?**

Visit [www.orenco.com](http://www.orenco.com) and use our Distributor Locator to connect with your nearest distributor for the full range of standard and custom offerings.

Or call us directly at (800) 348-9843.





Distributed By:

PO Box 768 • Old Saybrook, CT 06475  
Phone: (800) 221-4436 • Fax: (860) 577-7001  
[www.infiltratorwater.com](http://www.infiltratorwater.com)  
[info@infiltratorwater.com](mailto:info@infiltratorwater.com)



For U.S. Patents information visit [www.infiltratorwater.com/patents](http://www.infiltratorwater.com/patents). Other patents pending. Infiltrator, Quick4 and EZflow are registered trademarks of Infiltrator Water Technologies. Infiltrator Water Technologies is a wholly-owned subsidiary of Advanced Drainage Systems, Inc. (ADS).