

Pressure Regulating Wye Filter (PRYF)

APPLICATION

- Pressure-regulating Wye filters combine pressure regulation and filtration in one compact unit
- Ideal for low volume systems; attaches to 3/4 in. or 1 in. FPT connection point

FEATURES

- PRYF 30 is preset at 30 PSI
- PRYF 40 is preset at 40 PSI
- Constructed of high-impact acrylonitrile butadiene styrene (ABS) treated with UV inhibitors
- 200-mesh stainless steel filter blocks particulates that can potentially clog and damage emitters
- Removable flush cap with washer makes it easy to flush out component for cleaning and maintenance
- Fits into a 6 in. round valve box

OPERATING RANGE

- PRYF 30: 0.2 – 5 GPM flow range
- PRYF 40: 2.0 – 15 GPM flow range

SPECIFICATIONS

- Filtration: 200-mesh stainless steel screen
- Inlet pressure:
 PRYF 30 regulates 20 -150 PSI to 30 PSI
 PRYF 40 regulates 20 -150 PSI to 40 PSI

WARRANTY

- Limited one-year warranty



PRYF 30



PRYF 40

Part Number	Description
PRYF 30	3/4 in. MPT, 30 PSI Pressure Regulating Filter, 200 mesh
PRYF 40	1 in. MPT, 40 PSI Pressure Regulating Filter, 200 mesh