Inserta Wye™
Comparison Guide

The Inserta Wye Comparison Guide was designed to illustrate differences between Inserta Wye and other products. Inserta Wyes are for new, rehabilitation and repair installations and will provide:

- Reduction in labor hours and pipe materials
- Watertight*, testable connection every time
- Services connected where needed
- Eliminates glues, epoxies, grout and retightening of bands



Inserta Wye



Rubber Saddle Wye



PVC Wye Fitting

Testing	Air testable in most pipes, meets the testing requirements of ASTM D3212 at 10.8 psi (75 kPa). Field testable to ASTM F2187, C969 and F1417.	Test information limited and does not meet ASTM D3212 at 10.8 psi (75 kPa).	Meets the testing requirements of ASTM D3212 at 10.8 psi (75 kPa).
Installation	Installation instructions included with every tee to ensure coring the perfect hole. Minimum protrusion will not interfere with post-installation inspection. No straps or bands to re-tighten. No need to disturb backfill around the host pipe. Fast, effective and easy to install	No installation instructions on how to core the hole. Bands need to be installed around the host pipe and need to be re-tightened after 15 minutes. Backfill must be removed completely around the host pipe. Cannot be used on corrugated or ribbed host pipe.	Installation can only occur during new installation of mainline. Requires complete excavation. Limited versatility and adjustability. Cannot be used with corrugated or ribbed host pipe.
Mainline Adaptability	Will fit all common types and diameters of mainline pipe.	Limited to smooth exterior wall mainline pipe types.	Limited to PVC mainline only.
Lateral Connection	Will fit all common types of lateral pipe from 4”-8” (100-200 mm).	Limited lateral sizes and types.	Limited to PVC lateral types.

* Watertight performance depends on the type and condition of the mainline pipe. Contact your ADS representative about your specific application.

Build America, Buy America (BABA)
Inserta Wye lateral connection, manufactured in accordance with ASTM F477, complies with the requirements in the Build America, Buy America (BABA) Act.

ADS

adspipe.com

ADS “Terms and Condition of Sale” are available on the website, www.ads-pipe.com.
ADS, Inserta Wye™ and the Green Stripe are registered trademarks of Advanced Drainage Systems, Inc.
© 2026 Advanced Drainage Systems, Inc. 11350 08-26 MH