


- (1) - 3/8" HEX BOLTS WITH SEALING WASHERS AND SILICONE CAULK ARE NOT PROVIDED BY NYLOPLAST
- (2) - THE PROCESS OF SEALING AND, IF DESIRED, BOLTING FRAME TO BASIN MUST BE DONE IN THE FIELD

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH NYLOPLAST HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM, FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM NYLOPLAST.

©2010 NYLOPLAST

DRAWN BY	AWA	MATERIAL
DATE	2-12-03	
REVISED BY	NMH	PROJECT NO./NAME
DATE	2-23-15	
DWG SIZE	A	SCALE 1:10 SHEET 1 OF 1

	3130 VERONA AVE BUFORD, GA 30518 PHN (770) 932-2443 FAX (770) 932-2490 <a href="http://www.nyloplast-us.com">www.nyloplast-us.com</a>	
	<b>TITLE</b> 18-30 IN SEALED FRAME & COVER BOLTED TO DRAIN BASIN	
DWG NO.	7001-110-487	REV B