

NOTES:

1. BACKFILL MATERIAL AND COMPACTION LEVEL SHALL BE THE SAME AS SPECIFIED FOR THE INSTALLATION OF SANITITE HP PIPE ACCORDING TO PROJECT SPECIFICATIONS.


2. A STANDARD EXTERNAL SEAL MAY BE USED WHEN THE DIFFERENCE IN PIPE OUTSIDE DIAMETERS IS EQUAL TO OR LESS THAN 1". ADS PRODUCT CODE IS XX67MR, WHERE "XX" IS THE CONNECTING PIPE DIAMETER.

FOR CONNECTIONS WHERE THE DIAMETER DIFFERENCE IS GREATER THAN 1", A BUSHING MAY BE AVAILABLE FROM THE MANUFACTURER TO INCREASE THE SMALLER OF THE TWO DIAMETERS. ALTERNATIVELY, A CUSTOM EXTERNAL SEAL FROM THE MANUFACTURER IS REQUIRED.

3. CONNECTION WITH THE STANDARD EXTERNAL SEAL WILL BE CONCENTRIC. CONNECTIONS WHERE THE PIPE INVERTS MUST BE AT THE SAME ELEVATION WILL REQUIRE A CUSTOM EXTERNAL COUPLER PROVIDED BY THE MANUFACTURER.

4. EXTERNAL SEAL MAY BE USED TO CONNECT EITHER DUAL WALL (CORRUGATED) OR TRIPLE WALL SANITITE HP PIPE TO AN EXISTING PIPE. FOR DUAL WALL PIPE, THE EXTERNAL SEAL SHOULD BE PLACED SUCH THAT THE END CLAMPS ARE CENTERED OVER THE CROWN (PEAK) OF THE PIPE CORRUGATION.

5. INSTALLATION OF THE EXTERNAL SEAL SHOULD BE DONE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS TO ACHIEVE A WATERTIGHT JOINT.



© 2016 ADS, INC.

2	REV. ALLOWABLE DIAMETER DIFFERENCE	JLE	12/20/16	JLE
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

SANITITE HP TO DISSIMILAR PIPE CONNECTION
DRAWING NUMBER: STD-606

Advanced Drainage Systems, Inc.
4640 TRUEMAN BLVD
HILLIARD, OHIO 43026

DRAWN BY:	CKM
DATE:	12/6/11
CHK'D BY:	
SCALE:	NTS
SHEET:	1 OF 1