

## NOTES:

- EXCAVATE TRENCHES TO PROPER WIDTH, AND PROPER DEPTH AS REQUIRED BY STATE AND LOCAL CODES.
- 2. SMOOTH IRREGULARITIES IN THE EXCAVATION. A LEVEL, FLAT SURFACE IS REQUIRED.
- 3. ASSEMBLE BIODIFFUSER LEACHING CHAMBERS AND UNIVERAL ENDPLATES TOGETHER IN TRENCH(ES).
- INSTALL UNIVERSAL END CAPS AND SECURE IN PLACE WITH BACKFILL.
- 5. PUNCH OUT PIPE HOLE OPENINGS IN THE END PLATES AS NEEDED AND CONNECT INLET PIPES.

- FILL SIDEWALL AREA TO TOP CHAMBERS WITH NATIVE SOIL (COARSE SAND OR FINE GRAVEL MAY ALSO BE USED: NO HEAVY CLAY, SILT OR DEBRIS SHALL BE INCLUDED).
- 7. "WALK IN" FILL TO COMPACT SOIL ALONG SIDES OF BIODIFFUSER THIS IS VERY IMPORTANT TO ACHIEVE LOAD RATING.
- 8. COVER BIODIFFUSER LEACHING CHAMBERS TO A MINIMUM OF 12"
  OF GRANULAR COVER AFTER CONSOLIDATION FOR H-10
  APPLICATIONS. AVOID LARGE ROCKS OR DEBRIS IN COVER
  MATERIAL. COVER HEIGHTS AND LIVE LOADING LIMITS ARE
  IMPACTED BY BOTH SOIL TYPE AND COMPACTION
  REQUIREMENTS. CONTACT ADS WHEN POOR SOILS ARE
  ENCOUNTERED AND FOR MAXIMUM FILL HEIGHTS.

© 2016 ADS. INC.

2	FORMATTING UPDATES AND RENAMED	TJR	03/18/16		
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D	1

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

11in BIODIFFUSER SERIAL INSTALLATION

DRAWING NUMBER: STD-911A



DANIE STATES

DATE: 11/1/04

OCTO SY:

SOALE: NTS

SHEET OF