



TABLE 1: DIMENSIONS OF HP PIPE PRODUCTS AND CASING PIPE

	NOMINAL INSIDE DIAMETER	MAX OUTSIDE DIAMETER	*NOMINAL CASING SIZE
DUAL WALL	12" (300mm)	14.6" (371mm)	22" (559mm)
	15" (375mm)	17.8" (452mm)	24" (610mm)
	18" (450mm)	21.4" (544mm)	28" (711mm)
	21" (525mm)	24.9" (632mm)	32" (813mm)
	24" (600mm)	28.2" (716mm)	34" (864mm)
	30" (750mm)	35.6" (904mm)	42" (1067mm)
	TRIPLE WALL	30" (750mm)	35.7" (907mm)
36" (900mm)		41.4" (1052mm)	48" (1219mm)
42" (1050mm)		47.5" (1207mm)	54" (1372mm)
48" (1200mm)		53.9" (1369mm)	60" (1524mm)
60" (1500mm)		66.6" (1692mm)	78" (1981mm)

\* BASED ON LARGEST MANUFACTURED CASING SPACER RECOMMENDATION. SPECIFIC MANUFACTURERS MAY ALLOW FOR SMALLER CASING PIPE THAN SHOWN IN THE CHART.

NOTES:

1. THE CASING SPACER MANUFACTURER SHOULD BE CONTACTED FOR EXACT SIZING AVAILABILITIES, BUT IN GENERAL, MOLDED PLASTIC SPACERS PROVIDE SHORTER RUNNER HEIGHTS COMPARED TO STAINLESS STEEL CONFIGURATIONS. SOME CASING SPACER MANUFACTURES ARE: RACI, CASCADE WATERWORKS MANUFACTURING, PIPELINE SEAL & INSULATOR, INC, AND ADVANCE PRODUCTS & SYSTEMS, INC.
2. OTHER METHODS TO SUPPORT THE PIPE INVERT MAY BE USED, INCLUDING THE USE OF SKIDS IN BETWEEN MANUFACTURED CASING SPACERS OR FILLING THE VOID SPACE WITH SOIL OR GROUT MATERIAL, AT THE DISCRETION OF THE DESIGN ENGINEER.
3. TABLE 3 PROVIDES PUSH LENGTH VALUES FOR REFERENCE, HOWEVER SPECIFIC INSTALLATION CONDITIONS, INCLUDING THE CASING PIPE AND SPACER/BLOCKING MATERIALS, WILL IMPACT THE ALLOWABLE PUSH LENGTH. USING MANUFACTURED CASING SPACERS WILL HELP MINIMIZE THE RESISTANCE BETWEEN THE TWO SURFACES AND ALLOW FOR LONGER INSTALLATIONS.
4. REFER TO ADS TECHNICAL NOTE 5.18 FOR MORE INFORMATION REGARDING LINING OF CASINGS WITH SANITITE HP PIPE

TABLE 2: MAXIMUM UNSUPPORTED DISTANCES

PIPE DIAM.	RECOMMENDED MAXIMUM UNSUPPORTED DISTANCE *
12" - 24" (300mm - 600mm)	48" (1200mm)
30" - 60" (750mm - 1500mm)	84" (2100mm)

\* VALUES BASED ON THE PIPE GRADE VARYING NO MORE THAN 0.25-IN FROM TRUE GRADE ASSUMING THE PIPE IS FULL FOR THE DURATION OF ITS SERVICE LIFE. (SEE NOTE 2)

TABLE 3: PUSH LENGTHS FOR HP PRODUCTS

NOMINAL INSIDE DIAMETER	PUSH LENGTH *
12" (300mm)	400 ft (121m)
15" (375mm)	400 ft (121m)
18" (450mm)	400 ft (121m)
21" (525mm)	400 ft (121m)
24" (600mm)	400 ft (121m)
30" (750mm)	400 ft (121m)
36" (900mm)	300 ft (91m)
42" (1050mm)	300 ft (91m)
48" (1200mm)	300 ft (91m)
60" (1500mm)	300 ft (91m)

\* PUSH LENGTH IS PROVIDED AS GENERAL DESIGN GUIDANCE. CONTACT ADS IF ANTICIPATED LENGTHS EXCEED THE GIVEN VALUES.

© 2016 ADS, INC.

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT. NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

1	REV. DRAWING NAME OR NUMBER	TJR	01/28/16	
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

LINING OF CASINGS  
DETAIL (SANITITE HP)

DRAWING NUMBER: STD-110



4640 TRUENAME BLVD  
HILLIARD, OHIO 43026

DRAWN BY:	RJS
DATE:	10/12/15
CHK'D BY:	
SCALE:	NTS
SHEET:	1 OF 1