



**DURASLOT COUPLER BAND (C)
HARDWARE ASSEMBLY**

- A. Duraslot End Cap
- B. Duraslot Pipe
- C. Duraslot Coupler Band
- D. Duraslot Adapter
- E. ADS N-12 Pipe or HP Storm Pipe or Plain End Fitting
- F. Duraslot Grate Anchor Assembly
- G. 1/4" - 20 Flat Head Screw w/ Washer
- H. Duraslot Grate Connector
- I. Hex Head Assembly:
 (1) 5/16" x 3 1/2" Hex Head Screw
 w/ (2) Washers and (1) 5/16" - 18 Hex Nut

NOTE: - Slot height may vary per project
 - Each Cap (A) & Adapter (D) comes with Hardware - F, G
 - Each Coupler Band (C) comes with Hardware - G, H, I & J

© 2024 ADS, INC.

0	-	-	-	-
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT. NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

Duraslot Assembly

DRAWING NUMBER: STD-1480A



4640 TRUEMAN BLVD
 HILLIARD, OHIO 43026

DRAWN BY:	KJS
DATE:	03-26-2024
CHK'D BY:	
SCALE:	NTS
SHEET:	1 OF 1