



NOMINAL SLOT HEIGHT, in	PIPE Ø, in (mm)	W, in (mm)	H, in (mm)	PRODUCT #
2.5	4 (100)	2.00 (51)	2.50 (64)	GASDS
	6 - 12 (150 - 300)			GAMDS
	15 - 36 (375 - 900)			9900DS
6.0	4 - 36 (100 - 900)	2.50 (64)	6.00 (152)	GALDA
Custom (Variable)	4 - 36 (100 - 900)		2.50 - 36.00 (64 - 914)	9900DS

NOTES:

1. IF SLOT IS OPEN TOP, ONLY THE SLOT CAP IS PROVIDED AND IS COMPRESSION FITTED OVER THE END OF THE SLOT.
2. GRATE ANCHOR TO BE SET IN CONCRETE BACKFILL AND HOLDS THE GRATE IN TENSION.

1	Updated Layers & Logo	KJS	01/14/25	-
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

© 2025 ADS, INC.

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

Duraslot Grate Anchor Assembly
DRAWING NUMBER: STD-1413A



4640 TRUEMAN BLVD
HILLIARD, OHIO 43026

DRAWN BY:	KJS
DATE:	03-26-2023
CHK'D BY:	-
SCALE:	NTS
SHEET:	1 OF 1