

NOMINAL SLOT HEIGHT, in	PIPE Ø, in (mm)	W, in (mm)	H, in (mm)	PRODUCT #
2.5	4 (100)	2.00 (51)	2.50 (64)	GASDS
	6 - 12 (150 - 300)			GAMDS
	15 - 36 (375 - 900)			9900DS
6.0	4 - 36 (100 - 900)	2.50 (64)	6.00 (152)	GALDA
Custom (Variable)	4 - 36 (100 - 900)		2.50 - 36.00 (64 - 914)	9900DS

**NOTES:**


1. IF SLOT IS OPEN TOP, ONLY THE SLOT CAP IS PROVIDED AND IS COMPRESSION FITTED OVER THE END OF THE SLOT.
2. GRATE ANCHOR TO BE SET IN CONCRETE BACKFILL AND HOLDS THE GRATE IN TENSION.

© 2024 ADS, INC.

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

0	-	-	-	-
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

<b>Duraslot Grate Anchor Assembly</b>		 4640 TRUEMAN BLVD HILLIARD, OHIO 43026	DRAWN BY: KJS DATE: 03-26-2023 CVD BY: SCALE: NTS SHEET 1 OF 1
DRAWING NUMBER: STD-1413A			