



**TYPICAL BILL OF MATERIALS**

QUANTITY	MATERIAL	TOTAL
66	10' Length	660 LF
132	5' Lengths	660 LF
196	Coupler Bands	-----
4	Nyloplast Basins	-----
8	Slot Caps/Grate Anchors	-----

**TYPICAL BURIAL DEPTHS FOR SLOPED LINEAR DRAIN, in (mm)\***

POINT	4 in (100 mm) PIPE	6 in (150 mm) PIPE	8 in (200 mm) PIPE
A**	6.75 (171)	9.00 (229)	11.00 (279)
B	16.65 (423)	18.90 (480)	20.90 (531)

\* Burial depths listed here are for non-vehicular loads only.

\*\* If installed without an internal pipe slope, Point A burial depths may be used around the entire track.

**NOTES:**

1. SEE DETAIL 1464A OR 1464C FOR BACKFILL DESIGN INFORMATION.
2. OUTLET PIPE AND FITTINGS ARE NOT ACCOUNTED FOR HERE.
3. ALL DIMENSIONS ARE FOR REFERENCE ONLY.

© 2024 ADS, INC.

1	Notes Update	KJS	11/05/2024	-
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

**Duraslot & Duraslot XL Track & Field Layout**

DRAWING NUMBER: STD-1464B



4640 TRUEMAN BLVD  
HILLIARD, OHIO 43026

DRAWN BY	KJS
DATE	10-23-2024
CHK'D BY	-
SCALE	NTS
SHEET	1 OF 1