

CASE STUDY

Combined sewer overflow mitigated to meet Ohio EPA mandate

Norwalk, OH

OWNER

City of Norwalk, OH

ENGINEER

American Structurepoint, Columbus, OH

CONTRACTOR

Underground Utilities Inc., Monroeville, OH

INSTALLATION DATE

Winter-Spring 2025

PRODUCTS

1,000' (305 m) of 36" (900 mm) SaniTite® HP
8,300' (2,530 m) of 48" (1200 mm) SaniTite HP

DESCRIPTION

As part of a mandate by the Ohio Environmental Protection Agency (OEPA), the City of Norwalk had to address its last two remaining combined sewer overflows (CSO). The elimination of the CSOs, which is one of the city's largest projects in recent history, will rid the city and its residents of backups during major flooding events. During those flooding events, the sanitary sewers would back up into residences and also flow directly into streams, rivers and their tributaries.

To eliminate the backups, large diameter, triple-wall SaniTite HP, a polypropylene pipe, was chosen over traditional pipe types. 8,300' (2,530 m) of 48" (1200 mm) and 1,000' (305 m) of SaniTite HP was used for the main trunk lines.

Triple wall SaniTite HP has a smooth interior and exterior wall with corrugations in between. It is made from polypropylene for extra pipe stiffness and has dual gaskets for joint integrity. Polypropylene is ideal for sanitary applications as it is an inert material resistant to chemicals, abrasions, hot soils and caustic effluent. The light weight of the product provides the best installed cost.



adspipe.com

800-821-6710

