## DUAL WALL TO RCP MANHOLE ADAPTER FITTING WATER TIGHT CONNECTION

PART #	PIPE SIZE	А	В	OD
1222ANB	<b>12 in</b>	<b>12.0 in</b>	<b>48.0 in</b>	14.7 in
	(300 mm)	(305 mm)	(1219 mm)	(374 mm)
1522ANB	<b>15 in</b>	14.5 in	<b>46.6 in</b>	18.0 in
	(375 mm)	(368 mm)	(1184 mm)	(457 mm)
1822ANB	<b>18 in</b> (450 mm)	<b>18.0 in</b> (457 mm)	<b>45.6 in</b> (1157 mm)	<b>21.7 in</b> (551 mm)
2422ANB	<b>24 in</b>	24.0 in	<b>47.3 in</b>	28.5 in
	(600 mm)	(610 mm)	(1200 mm)	(724 mm)
3022ANB	<b>30 in</b>	24.0 in	<b>45.3 in</b>	<b>35.9 in</b>
	(750 mm)	(610 mm)	(1151 mm)	(912 mm)
3622ANB	<b>36 in</b> (900 mm)	24.0 in (610 mm)	<b>46.3 in</b> (1175 mm)	<b>42.1 in</b> (1068 mm)
4222ANB	<b>42 in</b>	24.0 in	<b>46.7 in</b>	48.5 in
	(1050 mm)	(610 mm)	(1186 mm)	(1233 mm)
4822ANB	<b>48 in</b> (1200 mm)	24.0 in (610 mm)	<b>47.3 in</b> (1200 mm)	<b>54.5 in</b> (1385 mm)
6022ANB	<b>60 in</b>	<b>30.0 in</b>	<b>54.0 in</b>	67.3 in
	(1500 mm)	(762 mm)	(1372 mm)	(1709 mm)

HDPE SMOOTH WALL CYLINDER

NOTE:

REQUIRES SERIES 65 GASKET (INCLUDED) IN FIELD TO MAKE WT CONNECTION



NOTE: ALL DIMENSIONS ARE NOMINAL

© 2023 Advanced Drainage Systems, Inc.