

INSERTA TEE® PROTRUSION CHART

Protrusion Percentage Per Mainline Diameter													
Inserta Tee Size	Maximum Protrusion	8"	10"	12"	15"	18"	21"	24"	30"	36"	42"	48"	60"
4"	0.60"	7.50%	6.00%	5.00%	4.00%	3.30%	2.90%	2.50%	2.00%	1.70%	1.40%	1.25%	1.00%
6"	0.60"	7.50%	6.00%	5.00%	4.00%	3.30%	2.90%	2.50%	2.00%	1.70%	1.40%	1.25%	1.00%
8"	0.60"		6.00%	5.00%	4.00%	3.30%	2.90%	2.50%	2.00%	1.70%	1.40%	1.25%	1.00%
10"	0.80"				5.30%	4.40%	3.80%	3.30%	2.70%	2.20%	1.90%	1.70%	1.30%
12"	0.90"					5.00%	4.30%	3.80%	3.00%	2.50%	2.10%	1.90%	1.50%
15"	1.00"						4.70%	4.20%	3.30%	2.80%	2.40%	2.10%	1.70%
18"	1.00"							4.20%	3.30%	2.80%	2.40%	2.10%	1.70%
24"	1.00"									2.80%	2.40%	2.10%	1.70%

Precise protrusion always depends on the type of mainline pipe used and the installation procedures followed. This chart is intended for reference only and is only for mainline pipes that are made from polyethylene, polyvinyl chloride, and ductile iron. These measurements should be approximate for mainlines that are solid wall, profile, closed profile, or corrugated. Mainlines that are clay or concrete do not protrude (0%).

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

INSERTA TEE PROTRUSION CHART

DRAWING NUMBER STD-1101



4640 TRUEMAN BLVD
HILLIARD, OH 43026

DRAWN BY:	HAK
DATE:	06/21/24
OK'S BY:	ENG
SCALE:	NTS
SHEET:	1