

## FLARED END SECTION SPECIFICATION

### Scope

This specification describes 12- through 36-inch (300 to 900mm) Flared End Sections for use in culvert and drainage outlet applications.

### Requirements

The Flared End Section shall be high density polyethylene meeting ASTM D3350 minimum cell classification 213320C; contact manufacturer for additional cell classification information. When provided, the metal threaded fastening rod shall be stainless steel.

### Installation

Installation shall be in accordance with ADS installation instructions and with those issued by state or local authorities. Contact your local ADS representative or visit [www.adspipe.com](http://www.adspipe.com) for the latest installation instructions.

	PIPE DIAMETER, in (mm)			
Diameter in (mm)	12 (300)	15 (375)	18 (450)	24 (600)
A in (mm)	6.5 (165)	6.5 (165)	7.5 (191)	7.5 (191)
B (max) in (mm)	10.0 (254)	10.0 (254)	15.0 (381)	18.0 (475)
H in (mm)	6.5 (165)	6.5 (165)	6.5 (165)	6.5 (165)
L in (mm)	25.0 (635)	25.0 (635)	32.0 (813)	36.0 (914)
W in (mm)	29.0 (737)	29.0 (737)	35.0 (889)	45.0 (1143)

\*Product detail may differ slightly from actual product appearance

