
DUAL WALL FABRICATED 30° BENDS 4" - 24" DIAMETER

| | PART# | PIPE SIZE | Α | JOINT |
|----|-----------|--------------------------|-------------------------|-------|
| ** | 0495AN | 4 in (100 mm) | 4.6 in (116 mm) | * |
| ** | 0695AN | 6 in (150 mm) | 5.5 in (139 mm) | * |
| ** | 0895AN | 8 in (200 mm) | 7.4 in (189 mm) | * |
| ** | 1095AN | 10 in (250 mm) | 8.4 in (214 mm) | * |
| | 1295AN | 12 in (300 mm) | 9.7 in (245 mm) | * |
| | 1295AN65B | 12 in (300 mm) | 5.8 in (146 mm) | WT |
| | 1595AN | 15 in (375 mm) | 12.4 in (315 mm) | * |
| | 1595AN65B | 15 in (375 mm) | 7.8 in (197 mm) | WT |
| | 1895AN | 18 in (450 mm) | 12.4 in (316 mm) | * |
| | 1895AN65B | 18 in (450 mm) | 6.7 in (170 mm) | WT |
| | 2495AN | 24 in (600 mm) | 15.9 in (404 mm) | * |
| | 2495AN65B | 24 in (600 mm) | 9.5 in (240 mm) | WT |


^{* =} PLAIN END

ST = SOIL TIGHT

WT = WATER TIGHT







WT (INCLUDES 2 GASKETS)



| DRAWING #: | 2210 | |
|--------------|------|-----------|
| DRAWN BY: | JCB | 04.06.06 |
| APPROVED BY: | JCB | 06.25.07 |
| REVISIONS: | TJR | 4/26/2016 |
| | | |
| | | |

NOTE: ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY

^{**} LIMITED AVAILABILITY. PLEASE SEE INJECTION MOLDED FITTING SECTION FOR OTHER AVAILABLE FITTINGS