Quick4® Heavy Duty Standard

Chambers

The heavy duty structural design of the Quick4 HD Standard Chamber will support non-commercial vehicular traffic loads*. Patent-pending Quick4 HD Standard Chamber fits in a 36″ wide trench and is ideal for curved or straight systems. The Contour Swivel Connection™ permits 10° turns, right or left. MultiPort endcap allows multiple piping options and eliminates pipe fittings.

Benefits

- Supports non-commercial vehicle loads with only 18" of cover
- Advanced contouring connections swivel 10-degrees, right or left
- Latching mechanism allows for quick installation
- · Four-foot chambers are easy to handle and install
- Certified by the International Association of Plumbing and Mechanical Officials (IAPMO)

MultiPort Endcap Benefits

- Eight molded-in inlets/outlets allow for maximum piping flexibility
- Multiple ports eliminate pipe fittings
- MultiPort endcap fits on either end of the chamber






* To achieve the non-commercial vehicular traffic loading design, the Quick4 HD Chamber must be installed as per the noncommercial vehicular traffic detail.


Quick4 Heavy Duty Standard Chamber Specifications	
Size	34" x 53" x 12" (864 mm x 1346 mm x 305 mm)
Effective Length	48" (1219 mm)
Louver Height	8" (203 mm)
Invert Height	8" (203 mm)

Contact Infiltrator's Technical Services
Department for assistance at 1-800-221-4436
or info@infiltratorwater.com


Quick4 Heavy Duty Standard Chamber



Multiport Endcap







Typical Trench View

