

DUAL WALL FABRICATED 60° REDUCING WYES 42"×4" - 42"×10" DIAMETER

PART#	PIPE SIZE	А	В	С	JOINT
4280AN60	42 x 4 in	51.9 in	33.5 in	39.7 in	*
	(1050 x 100 mm)	(1318 mm)	(850 mm)	(1009 mm)	
4280AN6065B	42 x 4 in	41.5 in	32.8 in	34.5 in	WT
	(1050 x 100 mm)	(1055 mm)	(833 mm)	(877 mm)	V V I
4281AN60	42 x 6 in	51.9 in	34.5 in	39.7 in	*
	(1050 x 150 mm)	(1318 mm)	(875 mm)	(1009 mm)	
4281AN6065B	42 x 6 in	41.5 in	33.7 in	34.5 in	WT
	(1050 x 150 mm)	(1055 mm)	(856 mm)	(877 mm)	VV I
4282AN60	42 x 8 in	57.1 in	36.2 in	42.3 in	*
	(1050 x 200 mm)	(1450 mm)	(919 mm)	(1075 mm)	
4282AN6065B	42 x 8 in	46.7 in	35.2 in	37.1 in	WT
	(1050 x 200 mm)	(1186 mm)	(894 mm)	(943 mm)	VVI
4283AN60	42 x 10 in	57.1 in	38.9 in	42.3 in	*
	(1050 x 250 mm)	(1450 mm)	(987 mm)	(1075 mm)	
4283AN6065B	42 x 10 in	46.7 in	37.6 in	37.1 in	WT
	(1050 x 250 mm)	(1186 mm)	(955 mm)	(943 mm)	V V I



PLAIN END



WT (INCLUDES 3 GASKETS)

* = PLAIN END ST = SOIL TIGHT WT = WATER TIGHT



DRAWING #:	2380	
DRAWN BY:	JCB	04.20.06
APPROVED BY:	JCB	06.26.07
REVISIONS:	NJP	06.14.07