



Use of Inserta Tee Hole Saw is required for installation of Inserta Tee fittings. Silver and Gold hole saws are wet diamond bit. Reference detail STD 1100 for installation instructions.

- Heavy Duty 1/2" drill motor recommended for coring into plastic mainlines.
- Heavy Duty 1/2" drill motor recommended when using silver hole saws (4"-8") into non-plastic mainlines.
- Heavy Duty 1/2" drill motor recommended when using gold hole saws (4"-10") into non-plastic mainlines.

Hole Saws for Coring machines are equipped with 1 1/4" x 7 (tread) female adapter nut.

Inserta Tee® Hole Saw Detail

Common Hole Saws												
Hole Saw Series	Mainline Pipe Type	Lateral Size	2" (50mm)	3" (75mm)	4" (100mm)	6" (150mm)	8" (200mm)	10" (250mm)	12" (300mm)	15" (375mm)	18" (450mm)	24" (600mm)
Red	Plastic	Hole Saw Size	-	-	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	-	-	-	-	-
		Hole Saw Depth			4 ½" (114mm)	4 ½" (114mm)	4 ½" (114mm)					
		Pilot Drill	-	-	12mm	12mm	12mm	-	-	-	-	-
Blue	Plastic	Hole Saw Size	2 ⅝" (67mm)	3 ¾" (95mm)	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	10 ⅞" (276mm)	12 ⅞" (327mm)	15 1⅜" (402mm)	19 1⅜" (503mm)	25 ⅝" (603mm)
		Hole Saw Depth	4 ½" (114mm)	6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)	7 ½" (191mm)	7 ½" (191mm)	7 ½" (191mm)	7 ½" (191mm)	10 ½" (267mm)
		Pilot Drill	12mm	12mm	12mm	12mm	12mm	¾"	¾"	¾"	¾"	¾"
Silver	Non-Plastic	Hole Saw Size	-	-	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	-	-	-	-	-
		Hole Saw Depth			6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)					
		Pilot Drill	-	-	10mm	10mm	10mm	-	-	-	-	-
Gold	Non-Plastic	Hole Saw Size	2 ⅝" (67mm)	3 ¾" (95mm)	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	10 ⅞" (276mm)	12 ⅞" (327mm)	15 1⅜" (402mm)	19 1⅜" (503mm)	25 ⅝" (603mm)
		Hole Saw Depth	7" (178mm)	7" (178mm)	7" (178mm)	7" (178mm)	7" (178mm)	7" (178mm)	7" (178mm)	8 ½" (216mm)	9 ½" (242mm)	11 ½" (292mm)
		Pilot Drill	¾"	¾"	¾"	¾"	¾"	¾"	¾"	¾"	¾"	¾"
Uncommon Hole Saws												
Orange	Air Testible Applications ADS HP Pipe	Hole Saw Size	-	-	4 ⅜" (111mm)	6 ⅜" (162mm)	8 ⅝" (219mm)	10 ¾" (273mm)	12 ¾" (324mm)	15 ¾" (400mm)	19 1⅜" (484mm)	-
		Hole Saw Depth	4 ½" (114mm)	6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)	7 ½" (191mm)	7 ½" (191mm)	7 ½" (191mm)	7 ½" (191mm)	7 ½" (191mm)
		Pilot Drill	-	-	12mm	12mm	12mm	¾"	¾"	¾"	¾"	-
Grey	Solid Wall PE	Hole Saw Size	-	-	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	-	-	-	-	-
		Hole Saw Depth			6 ½" (165mm)	6 ½" (165mm)	6 ½" (165mm)					
		Pilot Drill	-	-	¾"	¾"	¾"	-	-	-	-	-
Black	Plastic	Hole Saw Size	-	-	4 ½" (114mm)	6 ½" (165mm)	8 ¾" (222mm)	-	-	-	-	-
		Hole Saw Depth			7" (178mm)	7" (178mm)	7" (178mm)					
		Pilot Drill	-	-	¾"	¾"	¾"	-	-	-	-	-

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

INSERTA TEE HOLE SAW DETAIL

DRAWING NUMBER STD-1102



4640 TRUEMAN BLVD  
HILLIARD, OH 43026

DRAWN BY:	HAK
DATE:	1/17/24
OK'S BY:	ENG
SCALE:	NTS
SHEET:	1