

DUAL WALL FABRICATED 60° REDUCING WYES 36"×12" - 36"×24" DIAMETER

PART#	PIPE SIZE	А	В	С	JOINT
3684AN60	36 x 12 in	63.0 in	41.4 in	43.5 in	*
	(900 x 300 mm)	(1600 mm)	(1050 mm)	(1106 mm)	
3684AN6065B	36 x 12 in	52.5 in	39.4 in	38.3 in	WT
	(900 x 300 mm)	(1334 mm)	(1002 mm)	(972 mm)	V 1
3685AN60	36 x 15 in	63.0 in	47.4 in	43.5 in	*
	(900 x 375 mm)	(1600 mm)	(1203 mm)	(1106 mm)	
3685AN6065B	36 x 15 in	52.5 in	44.8 in	38.3 in	WT
	(900 x 375 mm)	(1334 mm)	(1138 mm)	(972 mm)	VVI
3686AN60	36 x 18 in	68.3 in	48.2 in	46.2 in	*
	(900 x 450 mm)	(1734 mm)	(1224 mm)	(1172 mm)	
3686AN6065B	36 x 18 in	57.8 in	45.5 in	40.9 in	WT
	(900 x 450 mm)	(1467 mm)	(1156 mm)	(1039 mm)	VVI
3687AN60	36 x 24 in	78.8 in	52.4 in	51.4 in	*
	(900 x 600 mm)	(2000 mm)	(1331 mm)	(1306 mm)	
3687AN6065B	36 x 24 in	68.3 in	49.3 in	46.2 in	WT
	(900 x 600 mm)	(1734 mm)	(1251 mm)	(1172 mm)	VVI



PLAIN END



WT (INCLUDES 3 GASKETS)

* = PLAIN END ST = SOIL TIGHT WT = WATER TIGHT



DRAWING #:	2375A	
DRAWN BY:	JCB	04.20.06
APPROVED BY:	JCB	06.26.07
REVISIONS:	NJP	06.14.07