

A°	A%
1	1.75%
2	3.50%
3	5.25%
4	7.00%
5	8.75%
6	10.50%
7	12.25%
8	14.00%
9	15.75%
10	17.50%


* MAXIMUM DEFLECTION FOR 4" - 30" ADS N-12/HANCOR DUAL WALL CORRUGATED HDPE PIPE IN ANY DIRECTION WITHIN A NYLOPLAST ADS N-12/HANCOR DUAL WALL BELL

** SEE ADS/HANCOR FOR MAXIMUM ALLOWABLE PIPE SLOPE & FOR AVAILABILITY OF CUSTOM BENDS

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH NYLOPLAST HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM, FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM NYLOPLAST.

©2013 NYLOPLAST

DRAWN BY	EBC	MATERIAL
DATE	09-10-09	
REVISD BY	CCA	PROJECT NO./NAME
DATE	09-04-13	
DWG SIZE	A	SCALE 1:16 SHEET 1 OF 1

	3130 VERONA AVE BUFORD, GA 30518 PHN (770) 932-2443 FAX (770) 932-2490 www.nyloplast-us.com
	TITLE NYLOPLAST CONNECTION TO ADS N-12/HANCOR DUAL WALL PIPE WITH SLOPE
DWG NO.	7001-110-369 REV C