
REDUCING TAP WYE (ST/WT CONNECTION)

PART #	PIPE SIZE	Α	В	С	OD
1880AN65BS	18 x 4 in	33.9 in	20.9 in	28.0 in	4.3 in
	(450 x 100 mm)	(861 mm)	(531 mm)	(711 mm)	(108 mm)
1881AN65BS	18 x 6 in	33.9 in	21.9 in	28.0 in	6.3 in
	(450 x 150 mm)	(861 mm)	(556 mm)	(711 mm)	(159 mm)
1882AN65BS	18 x 8 in	33.9 in	23.6 in	28.0 in	8.6 in
	(450 x 200 mm)	(861 mm)	(599 mm)	(711 mm)	(218 mm)
2480AN65BS	24 x 4 in	40.7 in	25.6 in	34.4 in	4.3 in
	(600 x 100 mm)	(1034 mm)	(650 mm)	(874 mm)	(108 mm)
2481AN65BS	24 x 6 in	40.7 in	26.6 in	34.4 in	6.3 in
	(600 x 150 mm)	(1034 mm)	(676 mm)	(874 mm)	(159 mm)
2482AN65BS	24 x 8 in	40.7 in	28.3 in	34.4 in	8.6 in
	(600 x 200 mm)	(1034 mm)	(719 mm)	(874 mm)	(218 mm)
3080AN65BS	30 x 4 in	49.4 in	30.8 in	42.3 in	4.3 in
	(750 x 100 mm)	(1255 mm)	(782 mm)	(1074 mm)	(108 mm)
3081AN65BS	30 x 6 in	49.4 in	31.7 in	42.3 in	6.3 in
	(750 x 150 mm)	(1255 mm)	(805 mm)	(1074 mm)	(159 mm)
3082AN65BS	30 x 8 in	49.4 in	33.5 in	42.3 in	8.6 in
	(750 x 200 mm)	(1255 mm)	(851 mm)	(1074 mm)	(218 mm)





DRAWING #:		
DRAWN BY:	JCB	05.07.07
APPROVED BY:	JCB	06.28.07
REVISIONS:	NJP	06.20.07