



**NOTES:**

- 1 - FOR BURIAL DEPTHS GREATER THAN 10' BUT NO MORE THAN 15', REFERENCE DRAWING STD-403A
- 2 - AVOID CONSTRUCTION LOADING ON DOME AND STRUCTURE PRIOR TO CONCRETE COLLAR INSTALLATION
- 3 - WEIR LOCATION, ORIENTATION AND FABRICATION TO BE DETERMINED BASED ON STUB LOCATION
- 4 - MAX 6FT WEIR HEIGHT. WEIR MAY REQUIRE ADDED SUPPORT WHEN EXCEEDING 2FT.
- 5 - 48" POLYPROPYLENE BASINS WITH WEIRS REQUIRE REVIEW BY ADS ENGINEERING

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

STANDARD DETAIL  
48" POLYPROPYLENE BASIN  
WITH WEIR PLATE



4640 TRUEMAN BLVD  
HILLIARD, OH 43026

DRAWING NUMBER 7009-110-019 A

DRAWN BY:	NMH
DATE:	02/02/23
OK'S BY:	
SCALE:	NTS
SHEET:	1 OF 1