## DUAL WALL FABRICATED 22.5° BENDS 4" - 24" DIAMETER


	PART#	PIPE SIZE	А	JOINT
**	0492AN	<b>4 in</b> (100 mm)	4.5 in (114 mm)	*
**	0692AN	6 in (150 mm)	5.4 in (137 mm)	*
**	0892AN	8 in (200 mm)	7.6 in (194 mm)	*
**	1092AN	<b>10 in</b> (250 mm)	7.8 in (197 mm)	*
	1292AN	<b>12 in</b> (300 mm)	9.6 in (244 mm)	*
	1292AN65B	<b>12 in</b> (300 mm)	5.8 in (146 mm)	WT
	1592AN	<b>15 in</b> (375 mm)	13.1 in (334 mm)	*
	1592AN65B	<b>15 in</b> (375 mm)	5.4 in (137 mm)	WT
	1892AN	18 in (450 mm)	14.3 in (363 mm)	*
	1892AN65B	18 in (450 mm)	6.9 in (174 mm)	WT
	2492AN	24 in (600 mm)	18.9 in (480 mm)	*
	2492AN65B	<b>24 in</b> (600 mm)	9.5 in (240 mm)	WT

<sup>\* =</sup> PLAIN END


ST = SOIL TIGHT

WT = WATER TIGHT

\*\* LIMITED AVAILABILITY. PLEASE SEE INJECTION MOLDED FITTING SECTION FOR OTHER AVAILABLE FITTINGS



PLAIN END



WT (INCLUDES 2 GASKETS)



DRAWING #:	2205	
DRAWN BY:	JCB	04.06.06
APPROVED BY:	JCB	06.25.07
REVISIONS:	TJR	4/26/2016

NOTE: ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY

© 2023 Advanced Drainage Systems, Inc.